

**(8 Belt Set)**

**530-535-566-567-568 Diamond Top**

**4- 7"x 525", 4- 7"x 531"**

**Mato Splice**

**BEST**

1003196

**Price: \$  
2123.00**

[purchase](#)



**530-535-566-567-568, Belts 3 Ply JD Diamond Top W/JD Mato HP Splice lace.  
(8 Belt Set) (4)- 7"x 525", (4)- 7"x 531" Mato Splice Lace**

**Heaviest Belt you can purchase!**

**Minimum combined orders \$75.00**

**100% USA Made, 100% American Quality 100% Americas Guaranteed belting from WCCO Belting Co Wahpeton, ND**

**The other guys are selling you Chinese or foreign belts guaranteed.**

**NO FOREIGN BELTS SOLD HERE! We sale NO or have we EVER!!! offered ANY FOREIGN BELTING at our company. NOR do we offer any type of so called 2nd's, BLEMISHED or so called BLEM belting, WE never have and WE never will. Even on our EBAY site WORLDLY BUYS are the same belts we offer here.**

**We have taken a lot of BAD mouthing from the following companies, if you would like foreign made belts we recommend go here to get them, we are sure they can help you. hay tool or us baler belts**

**BELTING SPECS:**

**Americas Belting**

**Technical Specification Sheet:**

**Style: DIAMOND TOP 330 x .035 Bottom Cover**

**Description: Conveyor Belting for Balers**

**Cleat/Pattern Height .158" (5/32")**

**Top Cover Gauge .013" (1/64")**

**Carcass Gauge .135" (1/8")**

**Bottom Cover Gauge .035" (1/32")**

**Overall Gauge .341" (11/32")**

**Approximate Wt./Ft<sup>2</sup> 1.69 lb**

**Belt Breaking Tensile 2640 lb./inch**

**Belt Modulus 25500 lb./inch**

**Mini Pulley Diameter 3.00 inch**

**Temperature Rating:**

**Minimum: - 40° F**

**Maximum: + 225° F**

**Fabric Construction 3 ply x 110 lb (330 lb.)**

**Warp: Polyester**

**Weft: Polyester**  
**Rubber Compound RMA Grade II SBR**  
**Tensile: 2000 PSI**  
**Durometer: 68 Shore A**  
**Maximum Roll Width: 68"**

**Minimum order \$75.00 If you want the BEST! 100% USA Made! NO FOREIGN MATERIALS! We sale nor offer NO FOREIGN BELTS at our company.**

**Our company is the only company to offer this 100% Warranty on our Raptor, X-Treme Belt products they will be above any OEM standards in quality, along with longer working endurance than any other belting in the USA and World Wide market we service. Our belts will come with warrants for a period of one (1)to(2) year after date of purchase, that products manufactured by it ( Product(s) ) will be free from defects, within normal industry allowances, of material and workmanship, when the Products are operated under normal service conditions, are properly installed and are used for the purpose for which have been subject they were sold by Company. There is NO warranty for normal wear and deterioration. Company does not Warrant Products which have been subject to misuse, negligence, carelessness, accident, overloading, improper maintenance, service adjustments, alterations, modifications or replacement. Belting Warranty**



**Belt&Lace**



**Alligator Rivet Fastener**  
American 2 Package Dual End 4 Locking Pins



**MADE IN U.S.A.**